



Apreamare 32 Comfort

1 ENGINES

2 * VOLVOPENTA D4-225 power 225 mhp / 165 kW at 3500 rpm

2 SPEED (knots)

	VOLVOPENTA D4-225	
maximum speed at medium load displacement	28	knots
cruising speed at medium load displacement	24	knots

3 RANGE (nautical miles)

	VOLVOPENTA D4-225	
maximum speed	180	n.m.
cruising speed	240	n.m.

4 MAIN SIZES

Loa = overall length (standard ISO 8666)	9,90	m.	32 ft. 6 in.
Lh = Hull length (standard ISO 8666)	8,50	m.	27 ft. 11 in.
Lg = waterline length (boat fully laden)	7,15	m.	23 ft. 5 in.
Max. beam	3,20	m.	10 ft. 6 in.
Depth under propellers (boat fully laden)	0,71	m.	2 ft. 4 in.
Displacement unladen	5,5	ton./lb.	12125
Displacement laden	7,1	ton./lb.	15653
Max.number of persons on board	8		
navigation category CE 2003/44	B		
certification modules	B + Aa (Sound Emission)		R.I.Na.

5 TECHNICAL DATA

Hull type : 14°/15° of deadrise . Warped hull with spray rails

H = Overall height from keel	3,85	m.	12 ft. 8 in.
H t = Minimum transport height from keel	3,38	m.	11 ft. 1 in.
P = pulpit	0,00	m.	0,00
Fuel tanks capacity	500	lt./US gals.	132
Water tanks capacity	200	lt./US gals.	53

Technical data, performance and range figures, designs and graphic reproductions contained herein have no certification value. They are purely descriptive and refer to standard models. Actual technical or descriptive specifications must be provided solely with regards to the craft being purchased. Therefore, any indications will be binding for the seller only if contained in the sales contract and in the relevant manual