



Apreamare 38 Comfort

1 ENGINES

2 * VOVLOPENTA D4-300 power 300 mhp / 221 kW at 3500 rpm

2 SPEED (knots)

	VOVLOPENTA D4-300	
maximum speed at medium load displacement	28	knots
cruising speed at medium load displacement	24	knots

3 RANGE (nautical miles)

	VOVLOPENTA D4-300	
maximum speed	180	n.m.
cruising speed	220	n.m.

4 MAIN SIZES

Loa = overall length (standard ISO 8666)	11,56	m.	37 ft. 11 in.
Lh = Hull length (standard ISO 8666)	9,98	m.	32 ft. 9 in.
Lg = waterline length (boat fully laden)	8,50	m.	27 ft. 11 in.
Max. beam	3,45	m.	11 ft. 4 in.
Depth under propellers (boat fully laden)	0,97	m.	3 ft. 2 in.
Displacement unladen	9	ton./lb.	19842
Displacement laden	11	ton./lb.	24251
Max.number of persons on board	10		
navigation category CE 2003/44	B		
certification modules	B + Aa (Sound Emission)		R.I.Na.

5 TECHNICAL DATA

Hull type : 14°/15° of deadrise . Warped hull with spray rails			
H = Overall height from keel	4,22	m.	13 ft. 10 in.
H t = Minimum transport height from keel	3,69	m.	12 ft. 1 in.
P = pulpit	n.a.		
Fuel tanks capacity	750	lt./US gals.	198
Water tanks capacity	230	lt./US gals.	61

Technical data, performance and range figures, designs and graphic reproductions contained herein have no certification value. They are purely descriptive and refer to standard models. Actual technical or descriptive specifications must be provided solely with regards to the craft being purchased. Therefore, any indications will be binding for the seller only if contained in the sales contract and in the relevant manual