



PRELIMINARY

APREAMARE GOZZO 35

1 ENGINES

1 * VOLVOPENTA D6-330 DPH power 330 mhp / 243 kW at 3500 rpm	STD
2 * VOLVOPENTA D3-200 DPS power 200 mhp / 147 kW at 4000 rpm	OPT

2 SPEED (knots)

	VP D4 230 DPS		VP D4 270
Maximum speed at medium load displacement	30	knots	30
Cruising speed at medium load displacement	25	knots	25

3 RANGE (nautical miles)

	VP D4 230 DPS		VP D4 270
Maximum speed	N.D.	n.m.	N.D.
Cruising speed	N.D.	n.m.	N.D.

4 MAIN SIZES

Loa = overall length (standard ISO 8666)	11,14	m.	36 ft. 7 in.
Lh = Hull length (standard ISO 8666)	9,95	m.	32 ft. 8 in.
Lg = waterline length (boat fully laden)	9,64	m.	31 ft. 8 in.
Max. beam	3,48	m.	11 ft. 5 in.
Depth under propellers (boat fully laden)	0,90	m.	2 ft. 11 in.
Displacement unladen	7,0	ton./lb.	15432
Displacement laden	9,0	ton./lb.	19842
Max.number of persons on board	10		
Navigation category CE 2003/44	B		
Certification modules	A1		R.I.Na.

5 TECHNICAL DATA

Hull type : deadrise . Warped hull with spray rails			
H = Overall height from keel	3,95	m.	12 ft. 11 in.
H t = Minimum transport height from keel	3,95	m.	12 ft. 11 in.
Fuel tank capacity	700	lt./US gals.	185
Fresh water tank capacity	200	lt./US gals.	53
Black water tank capacity	50	lt./US gals.	13

Technical data, performance and range figures, designs and graphic reproductions contained herein have no certification value. They are purely descriptive and refer to standard models. Actual technical or descriptive specifications must be provided solely with regards to the craft being purchased. Therefore, any indications will be binding for the seller only if contained in the sales contract and in the relevant manual